



Rolex 1066 Movement Parts (1)

Compiled by EmmyWatch - <https://www.emmywatch.com>



Calibre 1066

Base Calibre 1030

- Ø28.5mm
- Train: 18.000
- Automatic
- Calendar
- Sweep second
- Shock Proof

1:1



7080



7081



7082



7083



7084



7087



7086



7090



7151



7152



7154

EMMYWATCH
VINTAGE RESTORATIONS



7162



7163



7165



7167

2:1



6886



7085



7088



7091



7156 B



7164



7188



7089-1

même pièce Calibre	N°	Désignation	Designation	Designación	Bezeichnung	Designazione
1000	6886	Vis de bride	<i>Screw for : Bridle</i>	Tornillo de brida	<i>Schraube für Werk-befestigungsbügel</i>	Vite per brida di fissaggio
1036	7080	Roue de centre avec chaussée	<i>Center wheel with cannon pinion</i>	Rueda de centro con cañón de minutos	<i>Minutenrad mit Minutenrohr</i>	Ruota di centro con rocchetto dei minuti
1036	7081	Chaussée, haut. 2,65 mm	<i>Cannon pinion, height 2,65 mm</i>	Cañón de minutos, altura 2,65 mm	<i>Minutenrohr, Höhe 2,65 mm</i>	Rocchetto dei minuti, altezza 2,65 mm
1036	7082	Roue des heures, double denture, haut. 1,70 mm	<i>Double toothing hour wheel, height 1,70 mm</i>	Rueda de las horas, doble endentadura, altura 1,70 mm	<i>Stundenrad mit Doppelzahnung, Höhe 1,70 mm</i>	Ruota delle ore a doppia dentatura, altezza 1,70 mm
1036	7083	Roue calendrier	<i>Calendar wheel</i>	Rueda calendario	<i>Kalenderrad</i>	Ruota calendario
1036	7084	Sautoir de quantième	<i>Date jumper</i>	Muelle flexible de fecha	<i>Datumssperre</i>	Scattadata

1036	7085	<i>Screw for : Date jumper</i>
1036	7086	<i>Calendar yoke</i>
1036	7087	<i>Calendar yoke spring</i>
1036	7088	<i>Screw for : Calendar yoke spring</i>
1036	7089-1	<i>Jewel for calendar-ring</i>
1036	7090	<i>Date disc</i>
1036	7091	<i>Supporting screw for setting lever spring</i>
1065	7151	<i>Calendar ring</i>
1055	7152	<i>Bridle</i>
1065	7154	<i>Casing ring, ref. 6604-6605</i>
1036	7156 B	<i>Screw for : Calendar wheel</i>
1065 GMT	7162	<i>Balance cock</i>
1065 GMT	7163	<i>Stud holder</i>
1065 GMT	7164	<i>Screw for : Stud holder</i>
1065 GMT	7165	<i>Balance with Breguet hairspring, regulated</i>
1065 GMT	7167	<i>Bridge for self-winding mechanism</i>
	7188	<i>Set of screws for 1 watch movement</i>