



Seiko 4826A Movement Parts (1)

Compiled by EmmyWatch - <https://www.emmywatch.com>

Calibre No.

4826A

Jewels

7j

Style Name

SEIKO QUARTZ WATCH WITH SOLAR POWERED CELL

Characteristics :

Casing diameter : ϕ 25.6 mm

Maximum height : 4.8 mm

Frequency of quartz crystal oscillator : 32,768 Hz

(Hz=Hertz Cycle per second)

Driving system : Step motor system (6 poles)

Driving energy : Sunlight or artificial light energy

Regulation system : Trimmer condenser



Rapid-second adjustment : Second hand stops to the next ten-second mark

Calendar (day & date)

Instant setting device for day & date calendar

Bilingual change-over system for day of the week

Battery recharge indicator : Second hand moving in two second intervals serves as battery life indicator



122 680



131 680



221 680



225 680



231 680



241 680



261 611



271 680



281 680



282 680



354 680



383 680



384 680



386 680



389 680



390 560



391 680



444 680



480 680




526 680



556 838



760 680



801 550



802 838



808 680



810 680



817 610



868 680



☆870 852



873 680



963 838



980 680



981 680



4001 859



4002 682



4050 857



4146 680



4219 859



4239 680



4242 681



4455 680



4018 859



022 282



022 468



022 753



022 761



023 029



023 033



023 436



027 904



027 908

2/1

Calibre No. 4826A	Jewels 7j	Style Name SEIKO QUARTZ WATCH WITH SOLAR POWERED CELL
-----------------------------	---------------------	---

PART NO.	PART NAME	PART NO.	PART NAME
122 680	Center wheel bridge	011 406	Upper hole jewel for fourth wheel
131 680	Third wheel bridge	011 411	Upper cap jewel for step rotor
221 680	Center wheel & pinion	011 411	Lower cap jewel for step rotor
225 680	Cannon pinion	011 411	Upper hole jewel for third wheel
231 680	Third wheel & pinion	011 411	Lower hole jewel for third wheel
241 680	Fourth wheel & pinion	011 424	Upper hole jewel for second setting wheel
261 611	Minute wheel	022 282	Date driving wheel screw
271 680	Hour wheel	022 468	Center wheel bridge screw
281 680	Setting wheel	022 468	Third wheel bridge screw
282 680	Clutch wheel	022 468	Circuit block screw
354 680	Winding stem	022 468	Coil block screw
383 680	Setting lever	022 468	Setting lever axle spring screw
384 680	Yoke (Clutch lever)	022 468	Setting lever spring screw
386 680	Setting lever spring	022 468	Setting wheel ring screw
389 680	Setting lever axle spring	022 468	Screw for battery connection
390 560	Setting lever axle	022 468	Minus lead terminal screw
391 680	Second-setting lever	022 753	Day jumper screw
444 680	Upper frame for hole jewel of fourth wheel	022 753	Date dial screw
480 680	Setting wheel ring	022 761	Dial screw
526 680	Second-setting wheel	023 029	Tube for circuit block
556 838	Date finger	023 033	Tube for third wheel bridge screw
760 680	Second jumper	023 436	Reset lever pin
801 550	Date dial	027 904	Second jumper adjusting pin
802 838	Date driving wheel	027 908	Second setting lever adjusting pin
808 680	Date dial guard A		
810 680	Date jumper		
817 610	Intermediate date wheel		
868 680	Day finger		
☆870 852	Day star with dial disk		
873 680	Day jumper		
963 838	Snap for day star with dial disk		
980 680	Intermediate wheel for day-date correction		
981 680	Day-date corrector wheel rocker		
4001 859	Circuit block		
4002 682	Coil block		
4050 857	Circuit bridge plate		
4146 680	Step rotor		
4219 859	Insulator for battery connection		
4239 680	Rotor stator		
4242 681	Plus terminal of battery connection		
4455 680	Reset lever		
4018 859	Silver oxide battery with special treatment		

Remarks :

Day star with dial disk

☆870 852 (English ↔ Spanish)Used when both the crown and the calendar frame are located **3** o'clock position.

If any other type of day star with dial disk is required, specify the number printed on the disk.

☆↔ Please see remarks.

Part numbers in light letters are not shown in photos.