



Seiko 6205B Movement Parts (2)

Compiled by EmmyWatch - <https://www.emmywatch.com>

Calibre No.	6205B	Jewels	24j	Style Name	(Seikomatic Selfdater)
↳ Basic Calibre 6205B 17J Catalog No. 62-05-1					



Cal, 6205B



Characteristics

- Casing diameter : 27.60 ϕ mm
- Maximum height : 5.35 mm
- Vibrations per hour : 18,000
- Automatic winding with sweep second
- Calendar (date)
- "Diashock" Shock Resistant Device
- "Diafix" Oil Lubrication Device



11278



231617



251617



446610



500728



015421



011206



015411



015113

EMMYWATCH

VINTAGE RESTORATIONS

☆ ⇨ Please see remarks on the reverse page.

As for all other parts not shown here, please refer to the basic calibre
(Cal No. **6205B** 17J Catalog No. 62-05-1 Green page).

Calibre No.		Jewels	Style Name	
6205B		24j	(Seikomatic Selfdater)	
⇨ Basic Calibre 6205B 17J Catalog No. 62-05-1				
PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS	
112728	Barrel & train-wheel bridge	500728	Oscillating weight	
122720	Center wheel bridge	505610	Transmission wheel	
161740	Pallet cock	821690	Ball-bearing for oscillating weight	
171618	Balance cock	831610	Pawl lever with jewel	
191724	Framework for automatic device	835610	Ball-bearing holder	
205408	Complete barrel with arbor	836610	Transmission holder	
213408	Barrel arbor	837610	Pawl lever holder	
224800	Center wheel & pinion with cannon pinion	☆ 801870	Date dial	
225800	Cannon pinion	802720	Date driving wh	
231617	Third wheel & pinion	803720	Setting wheel lever complete	
☆ 241800	Sweep second wheel & pinion	808720	Date dial guard	
251617	Escape wheel & pinion	810720	Date jumper	
261720	Minute wheel	811720	Date jumper spring	
271800	Hour wheel	814720	Setting wheel lever plate	
282720	Clutch wheel	817720	Intermediate date wheel	
285408	Ratchet wheel	022150	Stud screw	
301610	Jewelled pallet fork & staff	022250	Pawl lever holder screw	
310610	Balance complete with stud	022251	Click screw	
315610	Balance staff	022252	Minute wheel bridge screw	
331610	Roller with jewel	022252	Transmission holder screw	
341610	Regulator	022253	Dial screw	
345610	Stud holder	022254	Framework screw for automatic device	
☆ 354720 } ☆ 354721 }	Winding stem	022258	Bridge screw	
381610	Click	022266	Setting lever axle spring screw	
383720	Setting lever	022351	Center wheel bridge screw	
384720	Yoke (Clutch lever)	022351	Pallet cock screw	
385720	Yoke spring (Clutch lever spring)	022458	Screw for oscillating weight	
387720	Minute wheel bridge	022461	Case screw	
388720	Setting lever spring	022462	Ratchet wheel screw	
389720	Setting lever axle spring	022659	Setting lever spring screw	
390720	Setting lever axle	022750	Bearing plate screw for sweep second wheel	
401610	Mainspring with slipping attachment	022755	Date dial guard screw	
446610	Bearing plate for sweep second wheel	022776	Ball-bearing holder screw	
491610	Dial washer	011104	Upper hole jewel for center wheel	
014233	Diashock upper frame	011104	Lower hole jewel for center wheel	
014244	Diashock lower frame	011307	Upper hole jewel for sweep second wheel	
014225	Diashock hole jewel with frame	011503	Upper hole jewel for pallet	
011210	Diashock cap jewel	011503	Lower hole jewel for pallet	
014217	Diashock spring	011112	Upper hole jewel for transmission wheel	
015421	Diafix upper hole jewel with frame for 3rd wheel	011112	Lower hole jewel for transmission wheel	
015421	Diafix lower hole jewel with frame for 3rd wheel	023151	Tube for bridge screw	
015411	Diafix upper hole jewel with frame for escape wheel			
015411	Diafix lower hole jewel with frame for escape wheel			
011206	Diafix cap jewel			
015113	Diafix spring			
Remarks :				
☆ 801870	Used for the case and dial where both the crown and the date frame are located at the 3 o'clock position. If the date dial of any other types is required, please inform clearly ① the Cal. No. ② the crown position and ③ the date frame position.			
☆ 354720	For the waterproof case having more than 36.5mm diameter.			
☆ 354721	For the waterproof case having less than 36.0mm diameter.			
☆ 241800...	241874 Sweep second wheel & pinion also acceptable.			

☆ ⇨ Please see remarks.

Items in light letters are not shown in photos; those parts are interchangeable with the basic calibre (Cal. No. 6205B 17J Catalog No. 62-05-1 Green page).